












Product comparison tables









Network video

Axis fixed network cameras

	AXIS 207W	AXIS M1011	AXIS M1011-W	AXIS M1031-W	AXIS M1054	AXIS M1103	AXIS M1104	AXIS M1113	AXIS M1114
									
Image sensor	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS
Lens	4 mm/F2.0 fixed iris	4.4 mm/F2.0 fixed iris	4.4 mm/F2.0 fixed iris	4.4 mm/F2.0 fixed iris	2.9 mm/F2.0 fixed iris	Fixed iris, CS mount 2.8 mm/F2.0 6 mm/F1.8	Fixed iris, CS mount 2.8 mm/F2.0 6 mm/F1.8	Varifocal 2.9 - 8.2 mm/F1.4 DC-iris, CS mount	Varifocal 2.8 - 8 mm/F1.2 DC-iris, CS mount
Horizontal angle of view	55°	47°	47°	47°	80°	2.8 mm: 66° 6 mm: 31°	2.8 mm: 80° 6 mm: 37°	65° - 25°	87° - 29°
Day and night									
Min illumination/light sensitivity (lux)	1 - 10,000	1 - 10,000	1 - 10,000	1 - 10,000 0 with LED on	1.2 - 100,000 0 with LED on	2.8 mm: 1.0 - 100,000 6 mm: 0.9 - 100,000	2.8 mm: 1.0 - 100,000 6 mm: 0.9 - 100,000	0.6	0.6
Video compression	MPEG-4 Motion JPEG	H.264 Motion JPEG MPEG-4	H.264 Motion JPEG MPEG-4	H.264 Motion JPEG MPEG-4	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG
Max video resolution (pixels)	640 x 480	640 x 480	640 x 480	640 x 480	1280 x 800 (1 MP) HDTV 720p	800 x 600	1280 x 800 (1 MP) HDTV 720p	800 x 600	1280 x 800 (1 MP) HDTV 720p
Frames per second	30 (640x480)	30 (640x480)	30 (640x480)	30 (640x480)	30 (1280x800) 30 (HDTV 720p)	30 (800x600)	30 (1280x800) 30 (HDTV 720p)	30 (800x600)	30 (1280x800) 30 (HDTV 720p)
Audio support	One-way Built-in mic			Two-way Built-in mic and speaker	Two-way Built-in mic and speaker				
Alarm in-/outputs	1/1				1/1				
Intelligent video	Motion detection Audio detection	Motion detection Tampering alarm	Motion detection Tampering alarm	Motion detection Audio detection Tampering alarm	Motion detection Audio detection Tampering alarm	Motion detection Tampering alarm	Motion detection Tampering alarm	Motion detection Tampering alarm	Motion detection Tampering alarm
Security	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption
Network	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS
Power	DC PoE splitter available	DC PoE splitter available	DC PoE splitter available	DC PoE splitter available	DC PoE IEEE 802.3af Class 2	PoE IEEE 802.3af Class 1	PoE IEEE 802.3af Class 1	PoE IEEE 802.3af Class 1	PoE IEEE 802.3af Class 1
Serial connectors									
Outdoor use						Requires housing	Requires housing	Requires housing	Requires housing
Other	Wireless		Wireless	Built-in PIR sensor, illumination LED, wireless	Built-in PIR sensor, illumination LED, digital PTZ, AVHS ⁽¹⁾	Digital PTZ, pixel counter, AVHS ⁽¹⁾	Digital PTZ, pixel counter, AVHS ⁽¹⁾	Digital PTZ, pixel counter, AVHS ⁽¹⁾	Digital PTZ, pixel counter, AVHS ⁽¹⁾
Axis Part #	0241-004	0302-004	0301-004	0300-004	0338-004	2.8mm: 0329-001 6mm: 0366-001	2.8mm: 0339-001 6mm: 0367-001	0340-001	0341-001









(1) AVHS - AXIS Video Hosting System with One-Click Camera Connection

Axis fixed network cameras









	AXIS P1311	AXIS 211^(a), AXIS 211W^(b)	AXIS 221	AXIS P1343^(a) AXIS P1343-E^(b)	AXIS P1344^(a) AXIS P1344-E^(b)	AXIS P1346^(a) AXIS P1346-E^(b)	AXIS P1347^(a) AXIS P1347-E^(b)	AXIS Q1755^(a) AXIS Q1755-E^(b)
								
Image sensor	1/4" progressive scan CMOS	1/4" progressive scan CCD ^(a) 1/4" progressive scan CMOS ^(b)	1/3" progressive scan CCD	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/3" (effective) progressive scan CMOS	1/2.5" progressive scan CMOS	1/3" progressive scan CMOS
Lens	4 mm/F1.2 fixed iris, CS mount	Varifocal 3 - 8 mm/F1.0 DC-iris, CS mount	Varifocal 3 - 8 mm/F1.0 DC-iris, CS mount	Varifocal 3 - 8 mm/F1.4 DC-iris, CS mount Remote back focus	Varifocal 3 - 8 mm/F1.2 DC-iris, CS mount Remote back focus	Varifocal 4 - 10 mm/F1.8 P-Iris ⁽¹⁾ , CS mount Remote back focus	Varifocal 3.5 - 10 mm/F1.6 P-Iris ⁽¹⁾ , CS mount Remote back focus	5.1 - 51 mm/F1.8 auto iris and autofocus 10x optical zoom 12x digital zoom
Horizontal angle of view	48°	67° - 27°	93° - 35°	59° - 25°	72° - 28°	61° - 29°	77° - 28°	50° - 5.4°
Day and night			Automatic	Automatic	Automatic	Automatic	Automatic	Automatic
Min illumination/light sensitivity (lux)	0.6 - 30,000	0.75	0.65 (color) 0.08 (B/W)	0.3 (color) 0.05 (B/W)	0.3 (color) 0.05 (B/W)	0.6 (color) 0.08 (B/W)	0.5 (color) 0.08 (B/W)	2 (color) 0.2 (B/W)
Video compression	H.264 Motion JPEG MPEG-4	MPEG-4 Motion JPEG	MPEG-4 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG
Max video resolution (pixels)	640 x 480	640 x 480	640 x 480	800 x 600	1280 x 800 (1 MP) HDTV 720p	2048 x 1536 (3 MP) HDTV 1080p	2560 x 1920 (5 MP) HDTV 1080p	HDTV 1080i (2 MP) HDTV 720p
Frames per second	30 (640x480)	30 (640x480)	45 (640x480) 60 (480x360)	30 (800x600)	30 (1280x800) 30 (HDTV 720p)	20 (2048x1536) 30 (HDTV 1080p) 30 (1600x1200)	12 (2560x1920) 20 (2048x1536) 30 (HDTV 1080p)	30 (HDTV 1080i) 30 (HDTV 720p)
Audio support	Two-way Built-in mic	Two-way Built-in mic ^(b)		Two-way Built-in mic ^(b)	Two-way Built-in mic ^(a)	Two-way Built-in mic ^(a)	Two-way Built-in mic ^(a)	Two-way Built-in mic ^(a)
Alarm in-/outputs	1/1	1/1	2/1	1/1	1/1	1/1	1/1	2 configurable inputs/outputs
Intelligent video	Motion detection Audio detection Tampering alarm	Motion detection Audio detection ^(b)	Motion detection Tampering alarm	Motion detection Audio detection Tampering alarm	Motion detection Audio detection Tampering alarm	Motion detection Audio detection Tampering alarm	Motion detection Audio detection Tampering alarm	Motion detection Audio detection Tampering alarm Gatekeeper
Security	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X ^(b)	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X
Network	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS
Power	DC PoE IEEE 802.3af Class 1	DC PoE IEEE 802.3af Class 2	AC/DC PoE IEEE 802.3af Class 2	DC ^(a) PoE IEEE 802.3af Class 2 ^(a) PoE Class 3/High PoE ^(b)	DC ^(a) PoE IEEE 802.3af Class 2 ^(a) PoE Class 3/High PoE ^(b)	DC ^(a) PoE IEEE 802.3af Class 3 ^(a+b) High PoE ^(b)	DC ^(a) PoE IEEE 802.3af Class 3 ^(a+b) High PoE ^(b)	AC/DC ^(a) PoE IEEE 802.3af Class 3 ^(a+b) High PoE ^(b)
Serial connectors			RS-232, RS-485					RS-422/RS-485
Outdoor use	Requires housing	Requires housing	Requires housing	Outdoor ready ^(b)	Outdoor ready ^(b)	Outdoor ready ^(b)	Outdoor ready ^(b)	Outdoor-ready ^(b)
Other	SD/SDHC card slot	Wireless ^(b)		WDR, digital PTZ, pixel counter, SD/SDHC card slot IP66 and NEMA 4X ratings ^(b)	WDR, digital PTZ, pixel counter, SD/SDHC card slot IP66 and NEMA 4X ratings ^(b)	WDR, digital PTZ, pixel counter, multi-view streaming, SD/SDHC card slot IP66 and NEMA 4X ratings ^(b)	WDR, digital PTZ, pixel counter, multi-view streaming, SD/SDHC card slot IP66 and NEMA 4X ratings ^(b)	SD/SDHC card slot analog video out, pan/tilt head support IP66 and NEMA 4X ratings ^(b)
Axis Part #	0293-004	0198-004 ^(a) 0270-004 ^(b)	0221-004	0320-001 ^(a) 0349-001 ^(b)	0324-001 ^(a) 0350-001 ^(b)	0328-001 ^(a) 0351-001 ^(b)	0343-001 ^(a) 0368-001 ^(b)	0304-001 ^(a) 0348-001 ^(b)

Notations (a) and (b) refer to the corresponding product models for the column; (1) AXIS P1346/-E and AXIS P1347/-E also supports DC-iris lens

Axis fixed dome network cameras

								
Image sensor	1/4" progressive scan CMOS	1/3" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS
Lens	3.0 mm/F2.0 fixed iris	3.6 mm/F1.8 fixed iris	2.9 mm/F2.0 fixed iris	2.9 mm/F2.0 fixed iris	3.0 mm/F2.0 fixed iris	2.9 mm/F2.0 fixed iris	Varifocal 2.8 - 10 mm/F1.7 fixed iris	Varifocal 2.8 - 10 mm/F1.7 fixed iris
Horizontal angle of view	66°	74°	66°	80°	66°	80°	66° - 18°	80° - 22°
Day and night								
Min illumination/ light sensitivity (lux)	1.5 - 10,000	3 - 10,000	1 - 100,000	1 - 100,000	1 - 10,000	1 - 10,000	0.9 - 100,000	0.9 - 100,000
Video compression	MPEG-4 Motion JPEG	MPEG-4 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG MPEG-4	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG
Max video resolution (pixels)	640 x 480	1280 x 1024 (1 MP)	800x600	1280x800 (1 MP) HDTV 720p	640 x 480	1280 x 800 (1 MP) HDTV 720p	800 x 600	1280 x 800 (1 MP) HDTV 720p
Frames per second	30 (640x480)	12 (1280x1024)	30 (800x600)	30 (1280x800) 30 (HDTV 720p)	30 (640x480)	30 (1280x800) 30 (HDTV 720p)	30 (800x600)	30 (1280x800) 30 (HDTV 720p)
Audio support								
Alarm in-/outputs								
Intelligent video	Motion detection Tampering alarm	Motion detection Tampering alarm	Motion detection Tampering alarm AXIS Camera Application Platform	Motion detection Tampering alarm AXIS Camera Application Platform	Motion detection Tampering alarm	Motion detection Tampering alarm	Motion detection Tampering alarm AXIS Camera Application Platform	Motion detection Tampering alarm AXIS Camera Application Platform
Security	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption
Network	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS
Power	PoE IEEE 802.3af Class 1	PoE IEEE 802.3af Class 1	PoE IEEE 802.3af Class 1	PoE IEEE 802.3af Class 1	PoE IEEE 802.3af Class 1	PoE IEEE 802.3af Class 1	PoE IEEE 802.3af Class 2	PoE IEEE 802.3af Class 2
Serial connectors								
Outdoor use								
Other		Digital PTZ	Rugged connectors for mobile surveillance, IP66, IP67 and NEMA 4X ratings, WDR, digital PTZ, pixel counter, AVHS ⁽¹⁾	Rugged connectors for mobile surveillance, IP66, IP67 and NEMA 4X ratings, WDR, digital PTZ, pixel counter, AVHS ⁽¹⁾	Recessed mounting, pixel counter	Recessed mounting, digital PTZ, pixel counter	Digital PTZ, pixel counter, AVHS ⁽¹⁾ Tamper resistant ^(a) Vandal resistant ^(b)	Digital PTZ, pixel counter, AVHS ⁽¹⁾ Tamper resistant ^(a) Vandal resistant ^(b)
Axis Part #	0281-004	0283-004	0330-001	0342-001	0284-004	0285-004	0336-001 ^(a) 0345-001 ^(b)	0337-001 ^(a) 0346-001 ^(b)

Axis fixed dome network cameras

	AXIS 216FD ^(a) AXIS 216FD-V ^(b) 	AXIS P3301 ^(a) AXIS P3301-V ^(b) 	AXIS 216MFD ^(a) AXIS 216MFD-V ^(b) 	AXIS P3304 ^(a) AXIS P3304-V ^(b) 	AXIS P3343 ^(a) AXIS P3343-V ^(b) 	AXIS P3344 ^(a) AXIS P3344-V ^(b) 	AXIS P3343-VE 	AXIS P3344-VE 
Image sensor	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/3" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS	1/4" progressive scan CMOS
Lens	Varifocal 2.8 - 10 mm/F1.3 DC-iris	Varifocal 2.8 - 10 mm/F1.3 DC-iris	Varifocal 2.8 - 10 mm/F1.3 DC-iris	Varifocal 2.8 - 10 mm/F1.7 DC-iris	Varifocal, DC-iris, remote focus and zoom 6 mm: 2.5-6 mm/F1.2 12 mm: 3.3-12 mm/F1.4	Varifocal, DC-iris, remote focus and zoom 6 mm: 2.5-6 mm/F1.4 12 mm: 3.3-12 mm/F1.6	Varifocal, DC-iris, remote focus and zoom 6 mm: 2.5-6 mm/F1.2 12 mm: 3.3-12 mm/F1.4	Varifocal, DC-iris, remote focus and zoom 6 mm: 2.5-6 mm/F1.4 12 mm: 3.3-12 mm/F1.6
Horizontal angle of view	73° - 20°	72° - 23°	100° - 27°	80° - 22°	6 mm: 72° - 34° 12 mm: 54° - 17°	6 mm: 87° - 40° 12 mm: 70° - 20°	6 mm: 72° - 34° 12 mm: 54° - 17°	6 mm: 87° - 40° 12 mm: 70° - 20°
Day and night					Automatic	Automatic	Automatic	Automatic
Min illumination/light sensitivity (lux)	1	1	2	0.9	6 mm: 0.2 (color), 0.04 (B/W) 12 mm: 0.3 (color), 0.05 (B/W)	6 mm: 0.3 (color), 0.05 (B/W) 12 mm: 0.4 (color), 0.06 (B/W)	6 mm: 0.2 (color), 0.04 (B/W) 12 mm: 0.3 (color), 0.05 (B/W)	6 mm: 0.3 (color), 0.05 (B/W) 12 mm: 0.4 (color), 0.06 (B/W)
Video compression	MPEG-4 Motion JPEG	H.264 Motion JPEG	MPEG-4 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG
Max video resolution (pixels)	640 x 480	640 x 480	1280 x 1024 (1 MP)	1280 x 800 (1 MP) HDTV 720p	800 x 600	1280 x 800 (1 MP) HDTV 720p	800 x 600	1280 x 800 (1 MP) HDTV 720p
Frames per second	30 (640x480)	30 (640x480)	12 (1280x1024) 30 (800x600)	30 (1280x800) 30 (HDTV 720p)	30 (800x600)	30 (1280x800) 30 (HDTV 720p)	30 (800x600)	30 (1280x800) 30 (HDTV 720p)
Audio support	Two-way Built-in mic	Two-way Built-in mic	Two-way Built-in mic	Two-way Built-in mic	Two-way Built-in mic	Two-way Built-in mic	Two-way	Two-way
Alarm in-/outputs	1/1	1/1	1/1	1/1	1/1	1/1	1/1	1/1
Intelligent video	Motion detection Audio detection Tampering alarm	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Audio detection Tampering alarm	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform
Security	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X
Network	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS
Power	DC PoE IEEE 802.3af Class 1	DC PoE IEEE 802.3af Class 2	DC PoE IEEE 802.3af Class 1	DC PoE IEEE 802.3af Class 2	PoE IEEE 802.3af Class 2	PoE IEEE 802.3af Class 2	PoE IEEE 802.3af Class 3	PoE IEEE 802.3af Class 3
Serial connectors								
Outdoor use							Outdoor ready	Outdoor ready
Other	Tamper resistant ^(a) Vandal resistant ^(b)	WDR, pixel counter, AVHS ⁽¹⁾ , ONVIF Tamper resistant ^(a) Vandal resistant ^(b)	Tamper resistant ^(a) Vandal resistant ^(b)	WDR, digital PTZ, pixel counter, AVHS ⁽¹⁾ Tamper resistant ^(a) Vandal resistant ^(b)	WDR, digital PTZ, SD/SDHC card slot, pixel counter Tamper resistant ^(a) Vandal resistant ^(b)	WDR, digital PTZ, SD/SDHC card slot, pixel counter Tamper resistant ^(a) Vandal resistant ^(b)	IP66 and NEMA 4X ratings, WDR, digital PTZ, pixel counter SD/SDHC card slot, vandal resistant	IP66 and NEMA 4X ratings, WDR, digital PTZ, pixel counter SD/SDHC card slot, vandal resistant
Axis Part #	0240-004 ^(a) 0268-004 ^(b)	0290-004 ^(a) 0292-004 ^(b)	0278-004 ^(a) 0279-004 ^(b)	0352-004 ^(a) 0353-004 ^(b)	6mm: 0307-001 ^(a) 0308-001 ^(b) 12mm: 0307-031 ^(a) 0308-031 ^(b)	6mm: 0326-001 ^(a) 0327-001 ^(b) 12mm: 0326-041 ^(a) 0327-041 ^(b)	6mm: 0299-001 12mm: 0299-031	6mm: 0325-001 12mm: 0325-041






Notations (a) and (b) refer to the corresponding product models for the column; (1) AVHS - AXIS Video Hosting System with One-Click Camera Connection

Axis pan/tilt/zoom network cameras

	AXIS 212 PTZ	AXIS 212 PTZ-V	AXIS 214 PTZ	AXIS 215 PTZ	AXIS 215 PTZ-E	AXIS 232D+	AXIS 233D
							
Image sensor	1/2" progressive scan CMOS	1/2" progressive scan CMOS	1/4" ExView HAD CCD	1/4" CCD	1/4" CCD	1/4" ExView HAD CCD	1/4" ExView HAD progressive scan CCD
Lens	2.7 mm/F1.8 fixed iris 3x instant zoom	2.7 mm/F1.8 fixed iris 3x instant zoom	4.1 - 73.8 mm/F1.3 auto iris and autofocus 18x optical zoom 12x digital zoom	3.8 - 46 mm/F1.6 auto iris and autofocus 12x optical zoom 4x digital zoom	3.8 - 46 mm/F1.6 auto iris and autofocus 12x optical zoom 4x digital zoom	4.1 - 73.8 mm/F1.4 auto iris and autofocus 18x optical zoom 12x digital zoom	3.4 - 119 mm/F1.4 auto iris and autofocus 35x optical zoom 12x digital zoom
Horizontal angle of view	140° - 44°	140° - 44°	48° - 2.7°	51.6° - 4.4°	51.6° - 4.4°	48° - 2.8°	55.8° - 1.73°
Day and night			Automatic	Automatic	Automatic	Automatic	Automatic
Min illumination/light sensitivity (lux)	10 lux wide mode 20 lux tele mode	10 lux wide mode 20 lux tele mode	0.3 (color) 0.005 (B/W)	1 (color) 0.3 (B/W)	1 (color) 0.3 (B/W)	0.3 (color) 0.005 (B/W)	0.5 (color) 0.008 (B/W)
Video compression	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG	MPEG-4, Motion JPEG
Max video resolution (pixels)	640 x 480	640 x 480	4CIF: 704 x 480	4CIF: 704 x 480	4CIF: 704 x 480	4CIF: 704 x 480	4CIF: 704 x 480
Frames per second (60/50 Hz)	30 (640x480) at max. zoom	30 (640x480) at max. zoom	30 (4CIF)	30 (4CIF)	30 (4CIF)	30 (4CIF)	30 (4CIF)
Pan/Tilt/Zoom	20 presets 140° pan 105° tilt Guard tour	20 presets 140° pan 105° tilt Guard tour	20 presets 340° pan 120° tilt	20 presets 360° pan via Auto-flip 180° tilt	20 presets 360° pan via Auto-flip 180° tilt	50 presets 360° endless pan 90° tilt Guard tour	100 presets 360° endless pan 180° tilt Guard tour
Audio support	Two-way, built-in mic	Two-way, built-in mic	Two-way	Two-way			Two-way
Alarm in-/outputs	1/1	1/1	1/1	1/1		4/4	4/4
Intelligent video	Motion detection Audio detection	Motion detection Audio detection	Motion detection Audio detection	Motion detection Audio detection	Motion detection	Motion detection	Motion detection Audio detection Auto-tracking
Security	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X
Network	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS
Power	DC PoE IEEE 802.3af Class 1	DC PoE IEEE 802.3af Class 1	DC	DC	Main power	AC/DC	AC/DC
Serial connectors							
Outdoor use			Requires housing	Requires housing	Outdoor ready	Requires housing	Requires housing
Other	Continuous motion 24/7	Continuous motion 24/7 Vandal-resistant		Auto-flip and E-flip	Auto-flip, E-flip, IP66 and NEMA 4X ratings	Continuous motion 24/7, WDR	Continuous motion 24/7, E-flip, image stabilizer, WDR
Axis Part #	0257-004	0280-004	0246-004	0274-004	0306-001	0253-001	0266-004





(1) Item sold separately

Axis pan/tilt/zoom network cameras

	 AXIS P5532	 AXIS P5534	 AXIS Q6032-E	 AXIS Q6034	 AXIS Q6034-E
Image sensor	1/4" ExViewHAD progressive scan CCD	1/3" progressive scan CCD	1/4" ExView HAD progressive scan CCD	1/3" progressive scan CCD	1/3" progressive scan CCD
Lens	3.6 - 104.4 mm/F1.43 auto iris and autofocus 29x optical zoom 12x digital zoom	4.7 - 84.6 mm/F1.6 auto iris and autofocus 18x optical zoom 12x digital zoom	3.4 - 119 mm/F1.4 auto iris and autofocus 35x optical zoom 12x digital zoom	4.7 - 84.6 mm/F1.6 auto iris and autofocus 18x optical zoom 12x digital zoom	4.7 - 84.6 mm/F1.6 auto iris and autofocus 18x optical zoom 12x digital zoom
Horizontal angle of view	53.1° - 2.0°	55.2° - 3.2°	55.8° - 1.73°	55.2° - 3.2°	55.2° - 3.2°
Day and night	Automatic	Automatic	Automatic	Automatic	Automatic
Min illumination/light sensitivity (lux)	0.5 (color) 0.01 (B/W)	0.74 (color) 0.04 (B/W)	0.5 (color) 0.008 (B/W)	0.74 (color) 0.04 (B/W)	0.74 (color) 0.04 (B/W)
Video compression	H.264, Motion JPEG	H.264, Motion JPEG	H.264, Motion JPEG	H.264, Motion JPEG	H.264, Motion JPEG
Max video resolution (pixels)	D1: 720x480	HDTV 720p 1280 x 720	D1: 720x480	HDTV 720p 1280 x 720	HDTV 720p 1280 x 720
Frames per second (60/50 Hz)	30 (D1)	30 (HDTV 720p)	30 (D1)	30 (HDTV 720p)	30 (HDTV 720p)
Pan/Tilt/Zoom	100 presets 360° pan via Auto-flip 180° tilt Limited guard tour	100 presets 360° pan via Auto-flip 180° tilt Limited guard tour	100 presets 360° endless pan 220° tilt Guard tour	100 presets 360° endless pan 180° tilt Guard tour	100 presets 360° endless pan 220° tilt Guard tour
Audio support	Two-way with multi-connector cable ⁽¹⁾	Two-way with multi-connector cable ⁽¹⁾		Two-way with multi-connector cable ⁽¹⁾	
Alarm in-/outputs	4 configurable inputs/outputs with multi-connector cable ⁽¹⁾	4 configurable inputs/outputs with multi-connector cable ⁽¹⁾		4 configurable inputs/outputs with multi-connector cable ⁽¹⁾	
Intelligent video	Motion detection Audio detection Advanced Gatekeeper	Motion detection Audio detection Advanced Gatekeeper	Motion detection Auto-tracking	Motion detection Audio detection Advanced Gatekeeper	Motion detection Auto-tracking Active Gatekeeper AXIS Camera Application Platform
Security	Multi-level passwords IP filtering, HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering, HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering, HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering, HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering, HTTPS encryption IEEE 802.1X
Network	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS
Power	AC/DC with multi-connector cable ⁽¹⁾ High PoE IEEE 802.3at (Midspan supplied)	AC/DC with multi-connector cable ⁽¹⁾ High PoE IEEE 802.3at (Midspan supplied)	High PoE IEEE 802.3at (Midspan supplied)	AC/DC with multi-connector cable ⁽¹⁾ High PoE IEEE 802.3at (Midspan supplied)	High PoE IEEE 802.3at (Midspan supplied)
Outdoor use	Requires housing	Requires housing	Outdoor ready	Requires housing	Outdoor-ready
Other	Auto-flip, E-flip, SD/SDHC card slot, IP51 rating, image stabilizer, WDR	Auto-flip, E-flip, SD/SDHC card slot, IP51 rating	Continuous motion 24/7, E-flip, SD/SDHC card slot, IP66 and NEMA 4X ratings, image stabilizer, WDR, Arctic Temperature Control	Continuous motion 24/7, E-flip, SD/SDHC card slot, IP51 rating	Continuous motion 24/7, E-flip, SD/SDHC card slot, IP66 and NEMA 4X ratings, AVHS ⁽²⁾ , ONVIF, Arctic Temperature Control
Axis Part #	0310-004	0314-004	0318-004	0363-004	0362-004









(1) Item sold separately, (2) AVHS - AXIS Video Hosting System with One-Click Camera Connection

Axis thermal network cameras

















	AXIS Q1910	AXIS Q1910-E	AXIS Q1921	AXIS Q1921-E
				
Image sensor	Uncooled Micro bolometer	Uncooled Micro bolometer	Uncooled Micro bolometer	Uncooled Micro bolometer
Lens	13 mm/F1.25	13 mm/F1.25	10 mm/F1.2 19 mm/F1.0	10 mm/F1.2 19 mm/F1.0 35 mm/F1.2 60 mm/F1.2
Horizontal angle of view	17°	17°	10 mm: 55° 19 mm: 29°	10 mm: 55° 19 mm: 29° 35 mm: 15° 60 mm: 9°
Detection range (m/yd.)	200/220 ^(a) 550/600 ^(b)	200/220 ^(a) 550/600 ^(b)	10 mm: 200/220 ^(a) 460/515 ^(b) 19 mm: 380/415 ^(a) 870/950 ^(b)	10 mm: 200/220 ^(a) 460/515 ^(b) 19 mm: 380/415 ^(a) 870/950 ^(b) 35 mm: 700/765 ^(a) 1610/1760 ^(b) 60 mm: 1200/1312 ^(a) 2760/3020 ^(b)
Sensitivity	NetD < 100 mK	NetD < 100 mK	NetD < 100 mK	NetD < 100 mK
Video compression	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG	H.264 Motion JPEG
Max video resolution (pixels)	160 x 128	160 x 128	384 x 288	384 x 288
Frames per second	8.3	8.3	8.3/30 ⁽¹⁾	8.3/30 ⁽¹⁾
Audio support	Two-way Built-in mic	Two-way	Two-way Built-in mic	Two-way
Alarm in-/outputs	2 configurable inputs/outputs	2 configurable inputs/outputs	2 configurable inputs/outputs	2 configurable inputs/outputs
Intelligent video	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform	Motion detection Audio detection Tampering alarm AXIS Camera Application Platform
Security	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X
Network	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS
Power	AC/DC PoE IEEE 802.3af Class 3	AC/DC PoE IEEE 802.3af Class 3	AC/DC PoE IEEE 802.3af Class 3	AC/DC PoE IEEE 802.3af Class 3
Serial connectors	RS-422/RS-485	RS-422/RS-485	RS-422/RS-485	RS-422/RS-485
Outdoor use	Requires housing designed for thermal cameras	Outdoor ready	Requires housing designed for thermal cameras	Outdoor ready
Other	Palette setting, SD/SDHC card slot, ONVIF	IP66 rating, palette setting, SD/SDHC card slot, ONVIF	Palette setting, SD/SDHC card slot, ONVIF	IP66 rating, palette setting, SD/SDHC card slot, ONVIF
Axis Part #	0334-001	0335-001	10mm: 0388-001 19mm: 0384-001	10mm: 0389-001 35mm: 0390-001 19mm: 0385-001 60mm: 0391-001

Notifications (a) and (b) refer to detection range measured for (a) humans 1.8 m x 0.5 m and (b) Vehicles 2.3 x 2.3 m; (1) 30 fps available for EU001 compliant countries such as U.S. and Canada

Accessories

Illuminators	
	
White light and infrared illuminators for indoor/outdoor surveillance in low light or complete darkness.	
AXIS T90A31 W-LED 30-60 Deg AXIS T90A26W-LED-100 Deg AXIS T90A16 W-LED 50 Deg AXIS T90A11 850nm 50 Deg AXIS T90A01 850nm 50 Deg PoE AXIS T90A20 850nm 120-180 Deg AXIS T90A21 850nm 50-100 Deg AXIS T90A33 850nm 10-20 Deg AXIS T90A33 850nm 30-60 Deg AXIS T90A42 850nm 30-60 Deg AXIS T90A40 850nm 120-180 Deg	5013-371 5013-261 5013-161 5013-111 5013-011 5013-201 5013-211 5013-331 5013-321 5013-421 5013-401
Power over Ethernet Midspans and Splitters	
	
Axis Power over Ethernet (PoE) and High PoE midspans and splitters offer an easy, cost-effective solution for powering network video products without the need for power outlets and electrical cabling.	
Power over Ethernet Midspans	
1-port High PoE 1-port (30 W) High PoE 1-port (60 W) 8-port 16-port	0226-004 5014-004 5700-401 5012-004 5012-014
Power over Ethernet Active Splitters	
High PoE 12V High POE 24V 5V	5014-501 5014-511 5008-001
Pan-Tilt Motor	
	
YP3040 Pan-Tilt Motor can be used with AXIS Q1755 and AXIS Q1910/-E cameras to enable basic pan and tilt capability. The motor can be mounted on walls, both indoors and outdoors.	
5502-461	
AXIS T8310 Video Surveillance Control Board	
	
AXIS T8310 Control Board is a modular system comprising of AXIS T8311 Joystick, which gives accurate control of PTZ functions of network cameras; AXIS T8312 Keypad, used for navigating between workspaces, cameras, views and PTZ presets; AXIS T8313 Jog Dial, used for navigating through recorded video. Each unit can be purchased and used separately or together.	
5020-001	
AXIS P7701 Video Decoder	
	
AXIS P7701 Video Decoder provides a simple monitoring solution by enabling analog or digital monitors to connect to and display live video from Axis network cameras and video encoders.	
0319-004	
AXIS P8221 Network I/O Audio Module	
	
AXIS P8221 provides eight I/O ports and audio capabilities to a network video surveillance system that either does not have such support or requires additional support.	
0321-004	
AXIS T8412 Installation Display	
	
AXIS T8412 is a battery-powered handheld device that greatly simplifies the field installation of both Axis network cameras and analog cameras. It displays live video from a camera and makes setting the viewing angle and focus at the installation site easier.	
5018-004	
AXIS Q8108-R Network Video Recorder	
	
AXIS Q8108-E is an 8-channel network video recorder (NVR) specially designed for public and commercial transportation applications. It provides uninterrupted in-vehicle recording in full frame rate HDTV resolution for up to 8 connected cameras.	
0332-031	










Axis network camera housings

	Part #	Product	Compatible with:
	5015-101 ^(a) 5015-204 ^(b)	AXIS T92A10^(a) / T92A20^(b) Housing Aluminum construction - Indoor/outdoor	AXIS M1103, AXIS M1104, AXIS M1113, AXIS M1114, AXIS P1311, AXIS 211, AXIS 211W, AXIS 221
	5010-001 ^(a) 5010-101 ^(b)	Dome Housing AXIS T95A00 110/240V AC^(a1) / T95A10 24V AC^{(b)2} Aluminum construction - Indoor/outdoor	AXIS 214 PTZ, AXIS 215 PTZ, AXIS 232D+, AXIS 233D
	5010-611	AXIS T95A61 Wall Bracket	Wall Bracket for AXIS T95A00 and T95A10 Dome Housing.
	5010-641	AXIS T95A64 Corner Bracket	Requires AXIS T95A61 Wall Bracket.
	5010-671	AXIS T95A67 Pole Bracket	Requires AXIS T95A61 Wall Bracket.
	24886	AXIS Indoor Fixed Wall Housing	AXIS M1103, AXIS M1104, AXIS M1113, AXIS M1114, AXIS P1311, AXIS 211, AXIS 221
	24887	AXIS Indoor Fixed Corner Housing	
	24888	AXIS Indoor Fixed Ceiling Housing	
	21899 ^(a) 24889 ^(b)	AXIS Fixed Housing - Indoor^(a) / Outdoor^(b) Aluminum construction - Indoor/Outdoor	AXIS M1103, AXIS M1104, AXIS M1113, AXIS M1114, AXIS P1311, AXIS 211, AXIS 221
	29892	AXIS Fixed Wireless Housing Aluminum construction - Outdoor	AXIS 211W
	25735 ^(a) 35540 ^(b)	AXIS Pendant Dome Indoor Clear^(a) / Smoked^(b) Plastic construction - Indoor	AXIS 214 PTZ, AXIS 215 PTZ, AXIS 232D+, AXIS 233D
	25733 ^(a) 35541 ^(b)	AXIS Pendant Dome Outdoor - Clear^(a) / Smoked^(b) Plastic construction - Indoor/outdoor	AXIS 214 PTZ, AXIS 215 PTZ, AXIS 232D+, AXIS 233D
	25734 ^(a) 35542 ^(b)	AXIS Pendant Vandal Dome - Clear^(a) / Smoked^(b) Aluminum construction - Indoor/outdoor	AXIS 214 PTZ, AXIS 215 PTZ, AXIS 232D+, AXIS 233D
	25736	Gooseneck Wall Mount	Gooseneck wall mount for the AXIS Pendant Dome
	25738	Parapet Mount	Parapet mount for the AXIS Pendant Dome
	22059	Corner Mount Adapter	Corner mount adaptor for the AXIS Pendant Indoor, Outdoor, and Vandal Dome Housings
	21896	Pole Mount Adapter	Pole mount adaptor for the AXIS Pendant Indoor, Outdoor, and Vandal Dome Housings.
	26349 ^(a) 26350 ^(b)	Ceiling Mount Extension 12"^(a) / 24"^(b)	Secures AXIS Pendant Dome housings to hard ceilings

Notations (a) and (b) refer to the corresponding product models for the column

1) 110 VAC input power 2) Requires AXIS PS-24 power supply (5000-001) 3) AXIS Q6032-E Pendant Kit included 4) Requires mounting tool (21776) 5) Requires 1.5"NPT threaded brackets

For more information, visit www.axis.com/products/video/accessories

	Part #	Product	Compatible with:
	5017-611	AXIS T91A61 Wall Bracket³ Includes mounting plate - White	AXIS Q6032-E, AXIS Q6034, AXIS Q6034-E, AXIS P5532, AXIS P5534, AXIS P33 Series Pendant Kit, AXIS P33-VE Series Pendant Kit, AXIS 216FD Pendant Kit
	5017-621	AXIS T91A62 Parapet Mount³	AXIS Q6032-E, AXIS Q6034, AXIS Q6034-E, AXIS P5532, AXIS P5534, AXIS P33 Series Pendant Kit, AXIS P33-VE Series Pendant Kit, AXIS 216FD Pendant Kit
	5017-631	AXIS T91A63 Ceiling Bracket³	AXIS Q6032-E, AXIS Q6034, AXIS Q6034-E, AXIS P5532, AXIS P5534, AXIS P33 Series Pendant Kit, AXIS P33-VE Series Pendant Kit, AXIS 216FD Pendant Kit
	5017-671	AXIS T91A67 Pole Bracket^{3 4}	AXIS Q6032-E, AXIS Q6034, AXIS Q6034-E, AXIS P5532, AXIS P5534, AXIS P33 Series Pendant Kit, AXIS P33-VE Series Pendant Kit, AXIS 216FD Pendant Kit
	5017-641	AXIS T91A64 Corner Bracket	Requires AXIS T91A61 Wall Bracket.
	5502-431	AXIS Q6032-E Pendant Kit	AXIS Q6032-E, AXIS Q6034, AXIS Q6034-E, AXIS P5532, AXIS P5534
	5502-351	AXIS P33 Series Pendant Kit	AXIS P3343, AXIS P3344
	5502-321	AXIS P33-VE Series Pendant Kit	AXIS P3343-VE, AXIS P3344-VE
	5502-021 ^(a) 5502-011 ^(b)	AXIS 216FD Pendant Kit⁵ - White^(a) / Black^(b)	AXIS 216FD, AXIS 216MFD, AXIS M3203, AXIS M3204, AXIS P3301, AXIS P3304




Axis video encoders

	1-channel video encoders					4- and 6-channel video encoders				
	AXIS 241S	AXIS M7001 ⁽²⁾	AXIS 243SA	AXIS 247S	AXIS Q7401 ^(3,4)	AXIS 240Q	AXIS 241Q ^(a) AXIS 241QA ^(b)	AXIS Q7404	AXIS 243Q	AXIS Q7406 ⁽⁴⁾
Video compression	MPEG-4 Motion JPEG	H.264 Motion JPEG	MPEG-4 Motion JPEG	MPEG-4 Motion JPEG	H.264 Motion JPEG	Motion JPEG	MPEG-4 Motion JPEG	H.264 Motion JPEG	MPEG-4 Motion JPEG	H.264 Motion JPEG
Max video resolution (pixels)	4CIF: 704x480	D1: 720x480	4CIF: 704x480	4CIF: 704x480	D1: 720x480	4CIF: 704x480	4CIF: 704x480	D1: 720x480	4CIF: 704x480	D1: 720x480
Frames per second H.264 (NTSC/PAL) in maximum resolution		30 (D1)			30 (D1)			30 (D1)		30 (D1) per channel
Frames per second Motion JPEG (NTSC/PAL) in maximum resolution	30 (4CIF)	30 (D1)	30 (4CIF)	30 (4CIF)	30 (D1)	6 (4CIF) per channel	30 (4CIF) using 1 channel, 30 (CIF) per channel using 4 channels	30 (D1)	30 (4CIF) per channel	30 (D1) per channel
Frames per second MPEG-4 (NTSC/PAL) in maximum resolution	21 (4CIF) 30 (2CIF)		30 (4CIF)	27 (4CIF) 30 (VGA)			21 (4CIF) using 1 channel, 20 (CIF) per channel using 4 channels		30 (4CIF) per channel	
Video source	1 BNC composite or Y/C video input ⁽¹⁾	1 BNC composite input	1 BNC composite or Y/C video input ⁽¹⁾	1 BNC composite input	1 BNC composite input	4 BNC composite inputs	4 BNC composite inputs	4 BNC composite inputs	4 BNC composite inputs	6 BNC composite inputs
Audio support			Two-way	One-way	Two-way		Two-way ^(b)	Two-way on one channel		
Alarm in-/outputs	4/4		4/4	1/1	4 configurable inputs/outputs	4/4	4/4	2 configurable inputs/outputs per channel	4/4	2 configurable inputs/ outputs per channel
Intelligent video	Motion detection Tampering alarm	Motion detection	Motion detection Audio detection Tampering alarm	Motion detection Audio detection	Motion detection Audio detection Tampering alarm	Motion detection Tampering alarm	Motion detection Audio detection ^(b) Tampering alarm	Motion detection Audio detection Tampering alarm	Motion detection Tampering alarm	Motion detection Tampering alarm
Pan/tilt/zoom support	●	●	●		●	●	●	●	●	●
Security	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X	Multi-level passwords IP filtering HTTPS encryption IEEE 802.1X
Network	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS	IPv4/v6, QoS
Power	DC	PoE IEEE 802.3af Class 2, supports power output for small covert camera	DC	DC PoE IEEE 802.3af Class 2/3, supports power output for analog camera	DC PoE IEEE 802.3af Class 2/3, supports power output for analog camera	DC	DC	DC		
Serial connectors	RS-232, RS-485	RS-422/RS-485	RS-232, RS-485		RS-422/RS-485	RS-232, RS-485	RS-232, RS-485	RS-422/RS-485	RS-485	RS-485
Standalone version	0186-004	0298-001	0256-004	0272-001	0288-004	0232-004	0185-004 ^(a) 0230-004 ^(b)	0291-004		
Blade version	0210-011					0232-024	0209-011 ^(a)		0261-001	0289-001

Notations (a) and (b) refer to the corresponding product models for the column; 1) Y/C video requires converter cable; 2) Covert camera included in AXIS M7001 Covert Surveillance Kit; 3) Supports local storage with SD/SDHC card; 4) ONVIF compliant

Rack solutions

Designed for high-density installations, Axis video encoder rack solutions accommodate multiple video encoder blades in the same rack.

	AXIS 291 1U Video Server Rack	AXIS Video Server Rack	AXIS Q7900 Rack
			
Number of slots	3	12	14
Blades supported	AXIS 240Q AXIS 241Q AXIS 241S AXIS 243Q AXIS Q7406	AXIS 240Q AXIS 241Q AXIS 241S	AXIS 240Q AXIS 241Q AXIS 241S AXIS 243Q AXIS Q7406
Maximum number of channels	18	48	84
Rack size	1U	3U	4U
Rack width	19"	19"	19"
Built-in power supply	Power supply	Replaceable power supply	Two redundant power supplies
Network	One Ethernet 10BASE-T/ 100BASE-TX/1000BASE-T (Gigabit Ethernet) port	One Ethernet 10BASE-T/ 100BASE-TX port per blade	Four Ethernet 10BASE-T/ 100BASE-TX/1000BASE-T (Gigabit Ethernet) ports
Axis Part #	0267-004	0192-004	0287-004

For more information, visit www.axis.com/products/video/video_server/

Video management software

AXIS Camera Station



AXIS Camera Station is a complete monitoring and recording system that is perfect for small- to mid-sized installations. It offers easy installation and setup with automatic camera discovery, a powerful Configuration Wizard and efficient management of the Axis network video products in the system.

10-camera base license	0202-004
4-camera base license	0202-054
20-camera add on license	0202-264
5-camera add on license	0202-014
1-camera add on license	0202-034
1-year software upgrade	0202-024

AXIS Camera Management



Powerful and efficient installation and management tool for Axis network video products. Available for free download.

Axis' Application Development Partners



A wide variety of software solutions for video surveillance, remote monitoring or broadcasting are available from more than 800 Axis Application Development Partners.

AXIS Video Hosting System



AXIS Video Hosting System is a server software for service providers. By installing the software to their own server or by using an assigned hosting partner, service providers can offer a true plug-and-play video monitoring service over the Internet for a large number of users.

AXIS Camera Station One



Software solution for viewing and recording live video from a single Axis network camera. Available for free download.

For more information, visit www.axis.com/products/video/software/

AXIS Mobile Monitor



AXIS Mobile Monitor software enables smartphones or Pocket PCs to quickly and easily access live video from Axis network video products. Available for free download.

AXIS Camera Application Platform



AXIS Camera Application Platform enables compatible applications, typically intelligent video applications, to be downloaded to Axis network video products.

About Axis Communications

Axis is an IT company offering network video solutions for professional installations. The company is the global market leader in network video, driving the ongoing shift from analog to digital video surveillance. Axis products and solutions focus on security surveillance and remote monitoring, and are based on innovative, open technology platforms.

Axis is a Swedish-based company, operating worldwide with offices in more than 20 countries and cooperating with partners in more than 70 countries. Founded in 1984, Axis is listed on the NASDAQ OMX Stockholm under the ticker AXIS. For more information about Axis, please visit our website at www.axis.com.

Distributed by: